

Culino & Culino Combi

Cooking and combi kettles



—HACKMAN—

Culino & Culino Combi

The renewed range of Culino cooking kettles and Culino Combi combi kettles with integrated bottom mixer presents a solid and safe production solution for every professional kitchen. Integrated bottom mixer and electric tilting are just a few of the many features that lighten the routine work and manual labour.

Culino and Culino Combi kettles are designed for easy and precise cooking. Digital display allows to set the desired temperature from the start, and electronic temperature control keeps the kettle in chosen temperature.

Electric tilting makes it safe to pour the food from the kettle. The kettle jacket is thermally insulated all the way round the kettle, which decreases heat loss and increases work safety.

Culino Combi models are equipped with sturdy integrated bottom mixers. All kinds of food, cold and warm, are mixed effortlessly and efficiently. Gentle stirring, mashing potatoes, grumbling of minced meat or mixing dough – all can be done in Culino Combi mixing kettle. The automatic mixing programmes are designed and tested by our chefs.

The bottom mixer is easy to use. It is operated from the control panel. The mixing tool is easy to place and easy to take out for cleaning. One mixing tool is suitable for all mixing, and the tool and the detachable scrapers are all dishwasher safe.

Equipped with the optional cooling attachment, operated by tap water or ice water, the Culino and Culino Combi kettles offer even wider range of use in the kitchen. The food is prepared from start to finish in the kettle: it is cooked, mixed and cooled.

All Culino kettles:

- net sizes 40, 60, 80, 100, 150, 200 and 300 liters of volume with big boiling spare
- electric or direct steam
- temperature range 0 – 120 °C, working pressure 1 bar
- all stainless steel construction, inner bowl of acid proof steel
- standard: electronic control, digital temperature display, electric tilting, removable solid lid, water mixer, safety equipment, fully insulated steam jacket
- options and accessories: installation frames, timer, automatic food water filling, cooling attachments, strainer plate, whipping grid, draw-off tap

Culino Combi kettles with mixer:

- integrated bottom mixer
- removable mixing tool with lift off scrapers, dishwasher safe
- mixing speed 20-110 rpm
- 4 preset mixing programmes
- autoreverse programme
- mixer safety features, e.g. the mixer is stopped when the lid is opened



- timer (optional) for automatic cook-and-hold function

- digital temperature display and water level indicator light

- 5 manual mixing speeds (20-110 rpm) with auto-reverse option at all speeds

- durable, user-friendly and easy to clean

- 4 pre-set mixing programs for standard recipes

- slanted position for increased ergonomics

- food water automatic (optional)



- on-off switches are fitted with indicator lights

Culino & Culino Combi

Culino Combi has an integrated bottom mixer. The mixer tool is securely in place also when tilting. The mixer tool is easy to remove thanks to the clean lifting handle. Removable scrapers. All parts are dishwasher proof.

New Culino can be connected to the control pillar of another Culino or Proveno combi-kettle.

Electric tilting is ergonomic and safe. 300 l kettles have hydraulic tilting.

Robust stainless steel lid. Solid lid is standard, a safety grid lid is optional. Safety grid lid enables adding of ingredients, water and spices while the mixer is activated. All parts are removable and dishwasher proof.

Optional integrated hand shower.

Control panel with clear push buttons for every function. Timer and water automatic are optional.



Fully insulated steam jacket for safe and energy-efficient cooking

Optional cooling attachments for direct cook-and-chill (with tap or chilled water)



A lift off safety grid enables continuous view into kettle and adding of ingredients, water and spices while the mixer is activated.



One mixing tool with lift off scrapers for all kind of mixing. Light but strong, unique shape.



Culino and Culino Combi can be equipped with a hand shower.



Culino Combi kneads doughs in a matter of minutes.

Culino & Culino Combi



CULINO, electric	Dimensions mm	Electric connection
Culino 40E	1047x620x1020	400V3N~ 12 kW 20A
Culino 60E	1047x620x1020	400V3N~ 12 kW 20A
Culino 80E (2006)	1154x690x1020	400V3N~ 16 kW 25A
Culino 100E	1154x690x1020	400V3N~ 16 kW 25A
Culino 150E	1360x940x1040	400V3N~ 20 kW 32A
Culino 200E (2006)	1360x940x1040	400V3N~ 30 kW 50A
Culino 300E	1560x1165x1040	400V3N~ 40 kW 63A

CULINO, steam	Dimensions mm	Electric connection	Steam consumption
Culino 40S	1047x620x1020	1N~ 0,3 kW 16A	12 kg/h
Culino 60S	1047x620x1020	1N~ 0,3 kW 16A	18 kg/h
Culino 80S	1154x690x1020	1N~ 0,3 kW 16A	24 kg/h
Culino 100S	1154x690x1020	1N~ 0,3 kW 16A	30 kg/h
Culino 150S	1360x940x1040	1N~ 0,3 kW 16A	45 kg/h
Culino 200S	1360x940x1040	1N~ 0,3 kW 16A	60 kg/h
Culino 300S	1560x1165x1040	3N~ 0,5 kW 16A	90 kg/h



CULINO COMBI, electric	Dimensions mm	Electric connection
Culino Combi 40E	1047x620x1020	400V3N~ 12,75 kW 25A
Culino Combi 60E	1047x620x1020	400V3N~ 12,75 kW 25A
Culino Combi 80E	1154x690x1020	400V3N~ 16,75 kW 32A
Culino Combi 100E	1154x690x1020	400V3N~ 16,75 kW 32A
Culino Combi 150E	1360x940x1040	400V3N~ 21,5 kW 40A
Culino Combi 200E	1360x940x1040	400V3N~ 31,5 kW 69A
Culino Combi 300E	1560x1165x1040	400V3N~ 41,5 kW 80A

CULINO COMBI, steam	Dimensions mm	Electric connection	Steam consumption
Culino Combi 40S	1047x620x1020	1N~ 1,0 kW 16A	12 kg/h
Culino Combi 60S	1047x620x1020	1N~ 1,0 kW 16A	18 kg/h
Culino Combi 80S	1154x690x1020	1N~ 1,0 kW 16A	24 kg/h
Culino Combi 100S	1154x690x1020	1N~ 1,0 kW 16A	30 kg/h
Culino Combi 150S	1360x940x1040	1N~ 1,8 kW 16A	45 kg/h
Culino Combi 200S	1360x940x1040	1N~ 1,8 kW 16A	60 kg/h
Culino Combi 300S	1560x1165x1040	3N~ 2,0 kW 16A	90 kg/h



Installation frames

Surface installation frame control pillar 40-100
Surface installation frame control pillar 150-300
Surface installation frame support pillar 40-300
Sub surface installation frame control pillar 40-100
Sub surface installation frame control pillar 150-300
Sub surface installation frame support pillar 40-300

Retrofit options

Lift off safety grid lid 40-60
Lift off safety grid lid 80-100
Lift off safety grid lid 150-200
Lift off safety grid lid 300

Accessories

Strainer plate Culino 40-60
Strainer plate Culino 80-100
Strainer plate Culino 150-200
Strainer plate Culino 300
Strainer plate extension Culino 300
Pouring adapter Culino 150-200
Pouring adapter Culino 300
Whipping grid Culino 40-60
Whipping grid Culino 80-100
Whipping grid Culino 150-200
Whipping grid Culino 300

Factory order options

Lift off safety grid lid 40-60
Lift off safety grid lid 80-100
Lift off safety grid lid 150-200
Lift off safety grid lid 300
Automatic food water filling
Shower
Timer
Cooling
HACCP facility
Draw off tap D1-std

Hackman

Ahjonkaarre

FI-04220 Kerava, Finland

Tel +358 204 3913

Fax +358 204 39 4306

international.sales@hackman.com

www.hackman.com